

SEPARATOR FOR BATTERY AND BATTERY USING IT

Patent number: JP2002025528
Publication date: 2002-01-25
Inventor: YAMAMOTO HIROYUKI; AOKI NOBUO; SANO TOYOHICO; HORI SHUJI; TANAKA TOMOFUMI; KIDA TATSUNOBU; KAMISASA TOSHIO
Applicant: DAIWA SPINNING CO LTD;; DAIWABO POYTECH KK
Classification:
- international: H01M2/16; H01M10/30
- european:
Application number: JP20000201652 20000703
Priority number(s): JP20000201652 20000703

Report a data error here

Abstract of JP2002025528

PROBLEM TO BE SOLVED: To obtain a separator for a battery which is superior in homogeneity of nonwoven fabric, which has an excellent liquid-retaining property and a sufficient strength of nonwoven fabric and which can contribute to improve a battery capacity without deteriorating the battery life, and obtain a battery which has outstanding battery characteristics such as improvement of self-discharging or the like. **SOLUTION:** One component is made from a component wherein (metha) acrylic acid metal salt is contained (MA-containing component (1)), and a fiber web is constituted from polyolefinic division-type composite fiber partitioned into not less than two by other components (2) and from polyolefinic fiber. After homogeneous nonwoven fabric is formed by the polyolefinic division-type composite fiber being divided through a disintegration/beating treatment, a pulper treatment in particular, at the time of slurry adjustment in a wet paper-making process or being divided through a water stream mixing treatment under a low pressure after a wet paper-making process, the separator for the battery capable of contributing to improve a battery capacity is obtained by applying a hydrophilic treatment such as a sulfonation treatment or the like.

